

# SureSoft<sup>®</sup> PelletsPlus<sup>®</sup> with Rust Buster<sup>®</sup>

## **Product Description**

- Sodium chloride is compacted into pellets, admixed, and quality control tested
- Conforms to the American Water Works Association Standard B200-17
- Certified by NSF to NSF/ANSI/CAN Standard 60

### **Physical Properties**

- Bulk Density: 61 lb/ft<sup>3</sup>
- Approximate Pellet Dimension:

Length:	1.125"
Width:	0.625"
Depth:	0.375"

#### Admixture

 Rust Buster<sup>®</sup> is a proprietary additive and iron removal agent for water softener resin maintenance

## **Production Location**

• Duluth, Minnesota - USA



Chemical Analysis							
Constituent		Units	Typical	Range			
Sodium Chloride	NaCl	(%)	99.82	99.34 - 100.0			
Calcium	Ca	ppm	194	0 - 541			
Magnesium	Mg	ppm	179	0 - 545			
Potassium	К	ppm	425	0 - 1114			
Sulfate	SO <sub>4</sub>	ppm	911	0 - 5458			
Water Insolubles		ppm	74	0 - 295			

Typical Screen Data						
U.S.S. Mesh	Tyler Mesh	Open (in)	Range %			
4	4	0.187	96.0	92 - 100		
Pan	Pan		4.0	0 - 8		

**Method of Analysis -** American Society for Testing and Materials Procedure E534. All other testing is from Compass Minerals' internal quality control procedures.

Packaging				Palletization						
UPC Code	New Product Code	Old Product Code	Description	Size (lb)	Volume (ft <sup>3</sup> )		Bags per Pallet	Dimensions (W "x L "x H")	Weight (lb)	Pallet Pattern (Ti x Hi)
041482-312403	765581	31240	Bag	40	0.61	27 x 13 x 3	63	48 x 40 x 35	2585	7 x 9

Compass Minerals 9900 West 109th Street – Suite 100 Overland Park, Kansas 66210 Ph: 800-755-7258 Fax: 800-359-7258 This information is based on our present state of knowledge and is intended to provide general notes on the product(s) supplied by us and their uses. The information should not be construed as a specific property promise or guarantee of the product(s). Chemical Analysis is based on the previous year's historical data.